

**MINOX**

Great Price. Great Performance.

**NEW**



**Everything a riflescope needs.**

**The new RS-4 series**

# Convincing in every situation.

Powerful performance. Smart design.

For a safe shot in any situation and all light conditions: The new RS-4 riflescopes with universal 4x zoom have everything a riflescope needs: high transmission, finely dimmable day/night illuminated reticle, a compact design and uncompromising stability.



- 1 | Large entrance pupil, high transmission
- 2 | Low-profile adjustment turrets
- 3 | Precise reticle adjustment with click detents
- 4 | Fine fiber optic illuminated reticle, adjustable in 10 steps
- 5 | Elegant design, slim and compact construction

For the best overview: Relatively large field of view at the respective magnification.



# The RS-4 riflescopes

All models at a glance

**NEW**



## RS-4 1-4x24

The perfect companion for driven and night hunts, also in conjunction with a clip-on attachment. Available in two reticle variants, #4 and #54.



## RS-4 2.5-10x42

The versatile rifle scope with an exceptionally short design, particularly suitable for use with clip-on attachments. Parallax setting from 10 m.



## RS-4 2.5-10x50

Reliable rifle scope for safe shooting at long ranges, in the field and in wide open areas. Parallax setting from 10 m.



## RS-4 3-12x56

Large objective lens for hunting from a high seat, high magnification for shooting at long distances and for mountain hunting. Parallax setting from 10 m. Also available with bullet drop compensation.

# RS-4 riflescopes – technical data

Model	1-4x24	2.5-10x50	2.5-10x42	3-12x56
Magnification	1-4x	2.5-10x	2.5-10x	3-12x
Field of view	40.0 – 10.0 m/100 m	16.0 – 4.0 m/100 m	16.0 – 4.0 m/100 m	13.3 – 3.3m/100 m
Angular field of view	22.6 – 5.7 °	9.1 – 2.3 °	9.1 – 2.3 °	7.6 – 1.9 °
Exit pupil	10 – 6 mm	10 – 5 mm	10 – 4.2 mm	10 – 4.6 mm
Twilight factor	2.8 – 9.8	7.1 – 22.4	7.1 – 20.5	8.5 – 25.9
Eye relief	90 mm			
Diopter range	-3 to +2 Diopters			
Light transmission	> 90 %			
Coating	M* Multicoating and hydrophobic coating			
Parallax compensation	100 m fix	10 m – ∞	10 m – ∞	10 m – ∞
Adjustment range	200 cm/100 m	200 cm/100 m	200 cm/100 m	200 cm/100 m
Adjustment per click	1 cm/100 m			
Clicks per revolution	80			
Reticle	#4 and #54	#4	#4	#4
Reticle image plane	2			
Illumination	yes, fiber optic			
Battery type	CR2032			
Tube diameter	30 mm			
Ocular diameter	46 mm			
Objective diameter	30 mm	56 mm	48 mm	62 mm
Objective filter thread	M28x0.75	M54x0.75	M46x0.75	M60x0.75
Length	274 mm	344 mm	295 mm	365 mm
Weight	471 g	661 g	633 g	757 g
Waterproof	yes, Nitrogen gas purged			
Operating temperature	-25 to +55 °C			
Storage temperature	-40 to +70 °C			
Shock resistance	1000 x 1000 g			
Warranty	10 Years (2 years on electronic parts)			



Find more information on our products and discover the whole MINOX product range on our website at [www.minox.com](http://www.minox.com)

## MINOX GmbH

Ziegelstadel 1 · D-88316 Isny im Allgäu, Germany  
Phone +49 (0) 75 62 / 98 13 50  
[info@minox.com](mailto:info@minox.com)

## Technical Service

Wilhelm-Loh-Str. 1  
D-35578 Wetzlar, Germany  
Phone +49 (0) 75 62 / 98 13 501  
[service@minox.com](mailto:service@minox.com)

## Availability Technical Service

Monday – Thursday  
08:30 – 12:00 and 13:00 – 17:30  
Friday  
8:30 – 15:30

## Your MINOX dealer



[facebook.com/minox.optics](https://facebook.com/minox.optics) · [youtube.com/minox](https://youtube.com/minox) · [instagram.com/minox.optics](https://instagram.com/minox.optics)